

**AMENDMENTS TO THE CLAIMS**

**Please amend the claims as follows:**

1. (Currently Amended)      An image reading apparatus, comprising:
  - a light source adapted to illuminate an original;
  - an image sensor adapted to scan said original and output electrical signals;
  - a first reference member which is arranged in an original scanning area of said image sensor in a sub-scanning direction;
  - a second reference member which is arranged in an area other than the original scanning area of said image sensor in the sub-scanning direction;
  - a memory adapted to store a predetermined time since said light source is turned on until a maximum of electrical signals output from said image sensor at the time said light source is turned on changes a predetermined rate;
  - a timer adapted to measure an on time since said light source is turned on;and
  - a controller adapted to determine whether the time measured by said timer reaches the predetermined time, in a case that the predetermined time has not elapsed, control said image sensor to scan said first reference member illuminated by said light source for acquiring a coefficient for uniformly changing level of the electrical signals, and in a case that the predetermined time has elapsed, control said image sensor to scan said second reference member illuminated by said light source only once for acquiring shading correction data in a main scanning direction.

2. (Canceled)

3. (Previously Presented)      The apparatus according to claim 1, further comprising:

        a correction unit which uses the shading correction data to perform shading correction on the electrical signals output from said image sensor.

4. (Original)      The apparatus according to claim 1, wherein said first and second reference members comprise white plates.

5. (Previously Presented)      The apparatus according to claim 4, wherein said first reference member is arranged at an end portion of a main scanning direction.

6. (Previously Presented)      The apparatus according to claim 1, wherein the determination by said controller is performed before each original sheet is read.

7. (Previously Presented)      The apparatus according to claim 6, further comprising:

        a feeder capable of successively supplying a plurality of original sheets,  
        wherein said controller performs the determination in a case that said feeder supplies each original sheet to a predetermined position.

8. (Previously Presented)      The apparatus according to claim 1, wherein in a case that a first original sheet is to be read after said light source is turned on, said controller controls said image sensor to scan said second reference member illuminated by said light source for acquiring shading correction data in the main scanning direction before start of read of the original sheet.

9. (Previously Presented)      The apparatus according to claim 8, wherein in a case that the first original sheet is to be read after said light source is turned on, and the predetermined time has not elapsed, said controller skips controlling said image sensor to scan said first reference member illuminated by said light source for acquiring the coefficient for uniformly changing level of the electrical signals.

10. - 14. (Canceled)

15. (Currently Amended)      A control method for an image reading unit having a light source adapted to illuminate an original, an image sensor adapted to scan said original and output electrical signals, a first reference member which is arranged in an original scanning area of said image sensor in a sub-scanning direction, and a second reference member which is arranged in an area other than the original scanning area of said image sensor in the sub-scanning direction, comprising:

        storing a predetermined time since said light source is turned on until a maximum of electrical signals output from said image sensor at the time said light source is turned on changes a predetermined rate;

measuring an on time since the light source is turned on;  
determining whether the measured time reaches the predetermined time;  
controlling said image sensor to scan the first reference member illuminated  
by said light source for acquiring a coefficient for uniformly changing level of the  
electrical signals in a case that the predetermined time has not elapsed; and  
controlling said image sensor to scan the second reference member  
illuminated by said light source only once for acquiring shading correction data in a  
main scanning direction in a case that the predetermined time has elapsed.

16. (Canceled)

17. (Previously Presented) The method according to claim 15, further  
comprising:

performing shading correction on the electrical signals output from the  
image sensor.

18. (Original) The method according to claim 15, wherein the first and second  
reference members comprise white plates.

19. (Previously Presented) The method according to claim 18, wherein the first  
reference member is arranged at an end portion of a main scanning direction.

20. (Previously Presented) The method according to claim 15, wherein said determination is performed before each original sheet is read.

21. (Previously Presented) The method according to claim 20, wherein the image reading unit further comprises a feeder capable of successively supplying a plurality of original sheets, and said determination is performed in a case that the feeder supplies each original sheet to a predetermined position.

22. (Previously Presented) The method according to claim 15, further comprising determining whether an original sheet is a first document sheet after the light source is turned on,

wherein in a case that the original sheet is determined to be the first document sheet, said controlling of said image sensor to scan the second reference member illuminated by said light source is executed before start of read of the original sheet regardless of a result of determining whether the measured time reaches the predetermined time.

23. (Previously Presented) The method according to claim 22, wherein in a case that the original sheet is determined to be the first document sheet, said controlling of said image sensor to scan the first reference member illuminated by said light source for acquiring a coefficient for uniformly changing level of the electrical signals is skipped regardless of the result of determining whether the measured time reaches the predetermined time.

24. (Canceled)

25. (Canceled)

26. (Currently Amended) An image reading apparatus comprising:

- a light source adapted to illuminate an original;
- an image sensor adapted to scan said original and output electrical signals;
- a reference member which is arranged in an area other than an original scanning area of said image sensor in a sub-scanning direction;
- a memory adapted to store a predetermined time since said light source is turned on until a maximum of electrical signals output from said image sensor at the time said light source is turned on changes a predetermined rate;
- a timer adapted to measure an on time since said light source is turned on;

and

- a controller adapted to determine whether the time measured by said timer reaches the predetermined time, and in a case that the predetermined time has

elapsed, control said image sensor to scan said reference member illuminated by said light source only once for acquiring shading correction data in a main scanning direction.

27. (Currently Amended) A control method for an image reading unit having a light source adapted to illuminate an original, an image sensor adapted to scan said original and output electrical signals, a reference member which is arranged in an area other than an original scanning area of said image sensor in a sub-scanning direction, comprising:

storing a predetermined time since said light source is turned on until a maximum of electrical signals output from said image sensor at the time said light source is turned on changes a predetermined rate;

measuring an on time since the light source is turned on;

determining whether the measured time reaches the predetermined time; and

controlling said image sensor to scan the reference member illuminated by said light source for acquiring a coefficient for uniformly changing level of the electrical signals in a case that the predetermined time has not elapsed; and

controlling said image sensor to scan the reference member illuminated by said light source only once for acquiring shading correction data in the main scanning direction in a case that the predetermined time has elapsed.